

PRODUCT DATA SHEET

Lubricants – Industrial

Converging the best and the most optimal, with incomparable power, enhancing performance at an amazing rate, **HYUNDAI XTeer** created by Hyundai's built-up technology will open the new world of Industrial lubricants.

XTeer Machine Oil

Description

Hyundai Oilbank XTeer Machine Oil is made from highly refined paraffin base oil. It is a product with excellent thermal stability, oxidation stability, anti-rust and anti-foaming properties, and is used as various industrial machine oil / flushing oil and plunger oil for casting work.

Application

- ✧ Various industrial oils and machine oils (especially low kinematic viscosity, suitable for various hydraulic systems)
- ✧ Flushing oil
- ✧ Plunger oil

Features / Benefits

- ✧ Excellent thermal stability and oxidation stability
- ✧ Prevents rust inside the machine
- ✧ Minimize the occurrence of oil mist to minimize the effect on castings
- ✧ Excellent antifoaming properties

Item	Unit	Method	Machine oil VG32	Machine oil VG68	Machine oil VG150	Machine oil VG320	Machine oil VG460
Specific gravity, 15/4°C	g/L	ASTM D 4052	854	861.6	868.4	876.8	877.8
Kinematic Viscosity, 40°C	cSt	ASTM D 445	29.37	68.08	149.9	329.8	450.8
Kinematic Viscosity, 100°C	cSt	ASTM D 445	5.17	9.12	15.33	25.79	32.43
Viscosity Index	-	ASTM D 2270	105	110	104	102	105
Flash point	°C	ADTM D 56	224	250	272	284	260
Pour point	°C	ASTM D 611	-33	-30	-30	-15	-18